



Rod/Line Weight Recommendations



Grain weights are calculated by the amount of line out beyond the rod tip while maintaining an anchor. Switch rod recommendations are for two-hand spey casting; subtract 60 grains for single-hand or overhead casting.

Model	Length	Line	Grain Window	Skagit G2	Skagit F.I.S.T.	Skagit Switch	Switch Streamer	Switch	Scandi Compact	Scandi Long	Rage Compact	Delta Spey II	Ultraspey
E3 SR 6110	11' 0"	6	330-390	390	N/A	390	WF6	WF6	360	N/A	390	N/A	N/A
E3 SR 7110	11' 0"	7	390-450	450	420	450	N/A	N/A	420	N/A	450	N/A	N/A
E3 SR 8110	11' 0"	8	450-510	510	480	510	N/A	N/A	480	N/A	510	N/A	N/A
E3 TH 6127	12' 7"	6	390-480	450	420	450	N/A	N/A	420	N/A	450	6/7	N/A
E3 TH 7130	13' 0"	7	480-570	510	480	510	N/A	N/A	480	480	510	7/8	N/A
E3 TH 8134	13' 4"	8	540-630	570	540	570	N/A	N/A	540	540	570	8/9	600
KING 9130	13' 0"	9	630-720	660	660	N/A	N/A	N/A	N/A	N/A	N/A	9/10	650
KING 10130	13' 0"	10	720-810	750	720	N/A	N/A	N/A	N/A	N/A	N/A	10/11	680
TR 4120	12' 0"	4	300-420	N/A	N/A	N/A	WF4	WF4.5	300	N/A	330	N/A	N/A
TR 5120	12' 0"	5	360-480	390	N/A	390	WF5	WF5.5	360	N/A	390	N/A	N/A
TR 6126	12' 6"	6	420-540	450	420	450	WF6	N/A	420	N/A	450	6/7	N/A
TR 7130	13' 0"	7	510-620	540	510	510	N/A	N/A	510	510	540	7/8	N/A
TR 8136	13' 6"	8	570-680	630	630	N/A	N/A	N/A	N/A	N/A	600	8/9	650
TR 9140	14' 0"	9	630-750	660	630	N/A	N/A	N/A	N/A	N/A	N/A	9/10	680
DH II 6126	12' 6"	6	390-480	450	390	450	WF6	N/A	390	N/A	450	6/7	N/A
DH II 6.5129	12' 9"	6.5	450-540	480	450	480	N/A	N/A	450	450	480	6/7	N/A
DH II 7130	13' 0"	7	480-590	510	480	510	N/A	N/A	480	480	510	7/8	N/A
DH II 8133	13' 3"	8	540-660	570	540	540	N/A	N/A	540	540	570	8/9	600
SR 3106	10' 6"	3	150-210	N/A	N/A	N/A	N/A	WF3	N/A	N/A	N/A	N/A	N/A
SR 4106	10' 6"	4	210-270	N/A	N/A	N/A	WF4	WF4	270	N/A	N/A	N/A	N/A
SR 5108	10' 8"	5	270-330	360	N/A	N/A	WF5	WF5	330	N/A	330	N/A	N/A
SR 61010	10' 10"	6	330-390	390	N/A	390	WF6	WF6	360	N/A	360	N/A	N/A
SR 71010	10' 10"	7	390-450	450	420	450	WF7	N/A	420	N/A	420	N/A	N/A
SR 81010	10' 10"	8	450-510	510	480	480	WF8	N/A	480	N/A	480	N/A	N/A
Classic 5109	10' 9"	5	270-330	330	N/A	N/A	WF5	WF5	300	N/A	330	N/A	N/A
Classic 6110	11' 0"	6	330-390	360	N/A	360	WF6	WF6	330	N/A	360	N/A	N/A
Classic 7110	11' 0"	7	390-450	450	420	450	N/A	N/A	420	N/A	450	N/A	N/A
Classic 8110	11' 0"	8	450-510	510	480	510	N/A	N/A	480	480	510	N/A	N/A
Classic 6126	12' 6"	6	390-510	450	420	450	WF6	N/A	420	N/A	450	6/7	N/A
Classic 7129	12' 9"	7	480-570	510	480	510	N/A	N/A	480	480	510	7/8	N/A
Classic 8130	13' 0"	8	540-660	570	540	N/A	N/A	N/A	540	540	570	8/9	600
FG 6126	12' 6"	6	390-480	450	420	450	WF6	N/A	420	N/A	450	N/A	N/A
FG 7129	12' 9"	7	480-590	510	480	480	N/A	N/A	480	480	480	6/7	N/A
FG 8130	13' 0"	8	540-660	570	540	N/A	N/A	N/A	540	540	540	7/8	600
FG 3106	10' 6"	3	150-210	N/A	N/A	N/A	N/A	WF3	N/A	N/A	N/A	N/A	N/A
FG 4108	10' 8"	4	210-270	N/A	N/A	N/A	WF4	WF4	270	N/A	N/A	N/A	N/A
FG 6110	11' 0"	6	330-390	360	N/A	360	WF5.5	WF6	330	N/A	330	N/A	N/A
FG 7110	11' 0"	7	390-450	420	390	420	N/A	N/A	390	N/A	390	N/A	N/A

Custom Cut Sink Tip Specs

Size	Per Ft.	Sink	Length	Loop
T7	7 gr	7 ips	10' or 18'	White
T10	10 gr	8 ips	10' or 18'	Orange
T14	14 gr	9.5 ips	10' or 18'	Brown
T18	18 gr	11 ips	10' or 18'	Black
CCT 200	10 gr	8 ips	20' sink tip looped at both ends	
CCT 330	18 gr	11 ips		

Echo Ion Reel Specs

Size	Weight	Diameter	Width
7/9	7.9 oz.	3.9"	1.3"
8/10	8.3 oz.	4.1"	1.5"
10/12	9.3 oz.	4.7"	1.5"

PolyLeader Specs

Type	Sink	5'	8'	10'	14'
Float	0 ips	16 gr	N/A	26 gr	40 gr
Hover	0.5 ips	17 gr	24 gr	28 gr	N/A
Int.	1.5 ips	18 gr	25 gr	30 gr	38 gr
Slow Sink	2.6 ips	20 gr	26 gr	34 gr	N/A
Fast Sink	3.9 ips	22 gr	30 gr	38 gr	52 gr
Super Fast	4.9 ips	36 gr	52 gr	56 gr	64 gr
Xtra Sup. Fast	6.1 ips	44 gr	78 gr	88 gr	112 gr

Running Line Specs

Size	Diameter
20 lb Super-DRI Ridge	.036"
30 lb Super-DRI Ridge	.040"
20 lb Supple	.030"
30 lb Ridge Extreme	.040"
50 lb Ridge Extreme	.045"
30 lb Miracle Braid	.028"
30 lb IMPACT	.012"
44 lb IMPACT	.015"